



NUMBER	PART	MATERIAL
1	HOUSING	ABS/PC
2	DUST CAP	PE
3	BOOT	TPR
4	FERRULE	ZrO2

NOTES:

1. LC DUPLEX TYPE.
2. INSERTION LOSS: <0.2DB.
3. OPERATING TEMPERATURE: -20°C to +70°C.
4. STORAGE TEMPERATURE: -40°C to +80°C
5. PACKAGING QUANTITY 100PIECE
6. THIS PRODUCT COMPLIES WITH ROHS.
7. COLOR: Blue, Gray, Aqua

Material		
ITEMS	SPECIFICATIONS	QTY
1		
2		
3		

x. ± 5	x° ± 5°	ECN.NO.	UNITS
.x ± 0.05	.x° ± 0.1°		mm
.xx ± 0.01	.xx° ± 0.05°	DRAWER	MAT'L
.xxx ± 0.001	.xxx° ± 0.01°	L	N/A
THIS DOCUMENT IS THE PROPRIETARY PROPERTY OF INTERNATIONAL.SUCH INFORMATION SHALL NOT BE REPRODUCED NOR DISCLOSED WITHOUT THE WRITTEN		APPD.	FINISH
			N/A
		RFV	DATE
		A	2018-4-12

		
TITLE:		
LC UNIBOOT SWITCHABLE WITH PULL-TAB CONNECTOR		
DWG NO.: GSCON01006		
	SCALE	SHEET
	N/A	1/1
	REV.	A