

NUMBER	PART	MATERIAL
1	HOUSING	ABS/PC
2	DUST CAP	PE
3	BOOT	TPR
4	FERRULE	ZrO2


NOTES:

- 1. LC SIMPLEX TYPE.
- 2. INSERTION LOSS: <0.2DB.
- 3. OPERATING TEMPERATURE: -20°C to +70°C.
- 4. STORAGE TEMPERATURE: -40°C to +80°C
- 5. PACKAGING QUANTITY 100PIECE
- 6. THIS PRODUCT COMPLIES WITH ROHS.
- 7. COLOR: BLUE, GREEN, GRAY, AQUA, E-V

Material		
ITEMS	SPECIFICATIONS	QTY
1		
2		
3		

x. ± 5	x° ± 5°	ECN.NO.	UNITS
.x ± 0.05	.x° ± 0.1°		mm
.xx ± 0.01	.xx° ± 0.05°	DRAWER	MAT'L
.xxx ± 0.001	.xxx° ± 0.01°	L	N/A
		APPD.	FINISH
			N/A
		RFV	DATE
		A	2018-4-12

THIS DOCUMENT IS THE PROPRIETARY PROPERTY OF INTERNATIONAL. SUCH INFORMATION SHALL NOT BE REPRODUCED NOR DISCLOSED



GAUSS
connectivity solutions

TITLE:
LC 2MM SIMPLEX CONNECTOR

DWG NO.: GSCON01002

	SCALE	SHEET	REV.
	N/A	1/1	A