



NUMBER	PART	MATERIAL
1	HOUSING	ABS/PC
2	DUST CAP	PE
3	BOOT	TPR
4	FERRULE	ZrO2

**NOTES:**

1. LC SIMPLEX TYPE.
2. INSERTION LOSS:<0.2DB.
3. OPERATING TEMPERATURE: -20°C to +70°C.
4. STORAGE TEMPERATURE: -40°C to +80°C
5. PACKAGING QUANTITY 100PIECE
6. THIS PRODUCT COMPLIES WITH ROHS.
7. COLOR:BLUE, GREEN, GRAY, AQUA, E-V

Material		
ITEMS	SPECIFICATIONS	QTY
1		
2		
3		

x. ± 5	x° ± 5°	ECN.NO.	UNITS	 <b>GAUSS®</b> <small>connectivity solutions</small>						
.x ± 0.05	.x° ± 0.1°		mm							
.xx ± 0.01	.xx° ± 0.05°	DRAWER	MAT'L	<b>TITLE:</b> <b>LC 3MM SIMPLEX CONNECTOR</b>						
.xxx ± 0.001	.xxx° ± 0.01°	L	N/A							
THIS DOCUMENT IS THE PROPRIETARY PROPERTY OF INTERNATIONAL.SUCH INFORMATION SHALL NOT BE REPRODUCED NOR DISCLOSED			APPD.	<b>DWG NO.:</b> <b>GSCON01001</b>						
			RFV							
			A							
			DATE	<table border="1"> <tr> <th>SCALE</th> <th>SHEET</th> <th>REV.</th> </tr> <tr> <td>N/A</td> <td>1/1</td> <td>A</td> </tr> </table>	SCALE	SHEET	REV.	N/A	1/1	A
SCALE	SHEET	REV.								
N/A	1/1	A								
			2018-4-12							