



NUMBER	PART	MATERIAL
1	HOUSING	ABS/PC
2	DUST CAP	PE
3	BOOT	TPR
4	FERRULE	ZrO2

NOTES:

1. LC DUPLEX TYPE.
2. INSERTION LOSS:<0.2DB.
3. OPERATING TEMPERATURE: -20 °C to +70 °C.
4. STORAGE TEMPERATURE: -40 °C to +80 °C
5. PACKAGING QUANTITY 100PIECE
6. THIS PRODUCT COMPLIES WITH ROHS.
7. COLOR:Blue,Gray,Aqua

Material		
ITEMS	SPECIFICATIONS	QTY
1		
2		
3		

x. ± 5	x° ± 5°	ECN.NO.	UNITS		
.x ± 0.05	.x° ± 0.1°		mm		
.xx ± 0.01	.xx° ± 0.05°	DRAWER	MAT'L	TITLE: LC UNIBOOT SWITCHABLE CONNECTOR	
.xxx ± 0.001	.xxx° ± 0.01°	L	N/A		
THIS DOCUMENT IS THE PROPRIETARY PROPERTY OF INTERNATIONAL.SUCH INFORMATION SHALL NOT BE REPRODUCED NOR DISCLOSED WITHOUT THE WRITTEN CONSENT OF INTERNATIONAL.			APPD.	DWG NO.: GSCON01008	
			RFV		FINISH
			A		N/A
			DATE		
			2018/4/12		
		SCALE	SHEET	REV.	
		N/A	1/1	A	